NOTES

GENERAL NOTES :-

ALL LEVELS ARE IN METRES DERIVED FROM GPS TRANSFORMATION.

GRID COORDINATES ARE ORDNANCE SURVEY NATIONAL GRID DERIVED FROM GPS TRANSFORMATION. GPS COORDINATES AND LEVELS SET AT ST01 (NO SCALE FACTOR APPLIED)

THIS DRAWING HAS BEEN PRODUCED WITH A PLOT SCALE ACCURACY OF 1:500

SERVICE COVERS INDICATED WHERE VISIBLE. PIPE INVERTS / DETAILS SURVEYED FROM SURFACE INSPECTION ONLY. GENERALLY DAMAGED COVERS AND COVERS WITHIN HIGHWAYS WILL NOT BE LIFTED

TREE SPECIES SHOULD BE CONFIRMED BY TREE SPECIALIST IF CRITICAL.

OVERHEAD CABLES ARE INDICATED USING REMOTE SURVEY METHODS AND ARE SUBJECT TO SEASONAL VARIATION, AND SHOULD BE TREATED AS APPROXIMATE.

SERVICE COVERS LOCATED UNDER PARKED VEHICLES/MOBILE STRUCTURES MAYBE OMITTED.

BURIED SERVICE COVERS WILL NOT BE INDICATED.

TOPOGRAPHICAL SURVEY/UTILITY KEY :-

(ht) – height
ø – diameter
Ø – geo trap
a/g – above ground
a/r – assumed route
av – air valve
bb – bellsha beacon
bd – back drop
bl – bed level
boll – bollard
bos – bottom of shaft
bt – telecom
c/b fence – closeboard fence
c/box – control box
catv – cable television
cl – cover level
con – conifer
cr – cable riser
cws – combined water sewer
d/chan – drainage channel
ejb – electric junction box
elec – electric
eot – end of trace
ep – electric pole
er – earth rod
f/bed – flower bed
fh – fire hydrant
fl – floor level
fs – fire switch
fws – foul water sewer
g – gully
g/run – gully run
gr – gas riser
h/chestnut – horse chestnut
h/thorn – hawthorn
ic – inspection cover
il – invert level
ill – illuminated
int – interceptor
lp – lamp post
mh – manhole cover
mkr – marker
o/h – over head
ol – off let
osa – off survey area
OSBM – ordnance survey bench mark
p & r fence – post & rail fence
pd – pit depth
pr – pipe riser
ptg – pipe to ground
pts – pipe to surface
re – rodding eye
ret wall – retaining wall
rs – road sign
rwp – rain water pipe
s/birch – silver birch
s/p – safety paving
sap – sapling
sec fence – security fence
sfc – soil filled chamber
si – spot light
sp – soil pipe
st – stop tap
sv – stop valve
svp – soil vent pipe
sws – storm water sewer
TBM – temporary bench mark
tfr – taken from records
ti – threshold level
toc – top of cap
top – top of pipe
tot – top of tank
tp – telecom pole
ts – traffic signal
t/s – trench scar
u/s – underside
utl – unable to lift
utr – unable to rod
uts – unable to survey
utt – unable to trace
vp – vent pipe
wfc – water filled chamber
wl – water level
wm – water meter
wp – waste pipe
wr – water riser

NORTH

AO-SHEET 2600B

UTILITY SURVEY KEY :-

HATCHED AREA
BOREHOLE
CPT
TRIAL PIT
HAND PIT
WINDOW SAMPLE

N — N — ELECTRIC CABLE
W — W — WATER PIPE
FOUL SEWER
STORM SEWER
COMBINED SEWER
D — D — DUCTS
TV — TV — CABLE TELEVISION
COM — COM — DATA CABLE
T — T — TELECOM CABLE
G — G — GAS PIPE
U — U — UNIDENTIFIED SERVICE
– – OTHER
CCTV — CCTV — CCTV
TL — TL — TRAFFIC LIGHT
O — O — OFFSET FILL
V — V — VENT
F — F — FUEL PIPE
GL — GL — GAUGE LINES
P — P — PIPE
AR — AR — ASSUMED ROUTE
TFR — TFR — TAKEN FROM RECORDS

DISCLAIMER :-

Electromagnetic techniques have been used in the location of underground services. The results are not infallible and trial excavations should be carried out to confirm service identification, positions and particularly depths, where these are critical. The completeness of the underground services information cannot be guaranteed.

This method of survey does not differentiate between live and dead services, and as such all services should be treated as live. This drawing may not include the location of all public services that may cross the site, therefore the relevant service drawings should be obtained from the appropriate utility company and used in conjunction with this drawing.

Private service pipes and cables in highways are not shown, but there presence should be anticipated.

Additional below ground structures or obstructions not shown on this drawing may be present. Reference should be made to historical plans and as-built drawings. Excavations in the vicinity of services should be carried out with due diligence ref: HSG47 document avoiding dangers from underground services

Please note that factors such as ground conditions, proximity of other utilities, material and method of construction have an influence on the quality of the data collected on site.

TSA Standards – "Even an appropriate and professionally executed survey may not be able to achieve a 100% detection rate."

UTILITY NOTES

0 5 10 20 30 40 50

MIDLAND SURVEY LTD

HEAD OFFICE
Cromwell House, Westfield Road, Southam, Warwickshire, CV47 0JH.
Tel: 01926 810811 Fax 01926 810812
E-Mail: mail@midlandsurvey.co.uk
www.midlandsurvey.co.uk

Client	REC LIMITED
Project	BBC CAVERSHAM, PEPPARD ROAD, READING, RG4 8TZ
Title	TOPOGRAPHICAL SURVEY
Date	OCTOBER 2016
Scale	1:500@A0
Dwg No	2600B/2
Surveyor	DCJ
Checked	DRC

Revisions

TOPOGRAPHICAL (LAND) SURVEYORS / UTILITY SURVEYORS
BUILDING MEASUREMENT SURVEYORS / 3D LASER SCANNING

©Copyright Midland Survey Ltd : Reproduction of this information is prohibited without written authorisation from Midland Survey Ltd.